Options

Pull-cord switch Interval time

Turn-on delay timer

Turn-off delay timer Humidity sensor Turn-on delay timer

Interval timer

• Humidity sensor

Dimensions [mm]

Sileo Design V2 100

**Overall dimensions** 

• Turn-off delay timer

Model

Option



## **SILEO DESIGN V2**



- Double-speed fan with air capacity up to 90 m³/h
- Specially designed mixed-flow impeller profile ensures high air capacity and low noise level.
- Casing and impeller are made of quality durable UV-resistant plastic.
- Backdraft damper for back flow prevention.
- The high ingress protection rating of IP45 makes the fan the ideal solution for the ventilation of bathrooms and shower rooms.
- The motor is mounted on special anti-vibration dampers.
- The exhaust pipe incorporates a specially designed air rectifier to reduce the air turbulence, increase pressure and lower the noise level.

s

• If the interval timer is enabled, the fan will turn on automatically

each 6, 12 of 24 hrs, and it will operate from 2 to 30 min, depending of

Sileo Design V2 100

т

•

•

н

• Ideal for intermittent or continuous ventilation.

Fixed turn-on delay time of 60 sec.

turn-off delay timer setting.

• Turn-off delay timer adjustable from 2 to 30 min.

• Humidity setpoint adjustable from 60 % up to 90 %.

٩B

В

200

L


130

L1

49

ØD


99





## Technical data

Model	Sileo Desi	Sileo Design V2 100	
	min	max	
Voltage [V/Hz]	220-240/50		
Power [W]	4.5	7	
Current [A]	0.029	0.052	
RPM [min <sup>-1</sup> ]	1850	2400	
Air flow [m³/h (l/s)]	60 (17)	90 (25)	
SFP [W/l/s]	0.27	0.28	
Noise level [dB(A)]	22	25	





Designation key			
Sileo Design	V2	100	н
Model	Two-speed motor	Spigot diameter	Option



## **SILENT & ENERGY SAVING**